Bohnenkamp Moving Professionals

10.05.2025

TYRES

Product group	Tyres
Item number	18692448
Valid tyre size	20 x 10.00 - 10
LI / SI / PR	93 A6, 6 PR
TL/TT	TL
Brand	Trelleborg
Tread pattern	T539





Notes and features

• Combination tread pattern for green areas, agriculture, industrial or high-speed operations.

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

Bohnenkamp Moving Professionals

Technical Informations

Item number	18692448
EAN	8059971011302
Valid tyre size	20 × 10.00 - 10
LI / SI / PR	93 A6, 6 PR
TL/TT	TL
Brand	Trelleborg
Tread pattern	Т539
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	7,86
Recommended rim size	7.00
Permitted rim size	8.50
Maximum air pressure [bar].	2,40
Section width (mm)	242
Outer diameter of tyre [mm].	512
Stat. radius (SLR) [mm]	233
Rolling circumference [mm].	1533
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
93 A6	650	30		2,40	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.