

TYRES

|                 |                     |
|-----------------|---------------------|
| Product group   | Tyres               |
| Item number     | 19211086            |
| Valid tyre size | 4.10 - 4            |
| LI / SI / PR    | 14 A4 / 25 A4, 2 PR |
| TL/TT           | TL                  |
| Brand           | Kenda               |
| Tread pattern   | K398A Polar Trac    |



Notes and features

- The Kenda K398A Polar Trac was specially developed for use on snow blowers.
- Its tread pattern enables excellent traction on slush, snow and ice.

## Technical Informations

|                              |                     |
|------------------------------|---------------------|
| Item number                  | 19211086            |
| EAN                          | 5707562523996       |
| Valid tyre size              | 4.10 - 4            |
| LI / SI / PR                 | 14 A4 / 25 A4, 2 PR |
| TL/TT                        | TL                  |
| Brand                        | Kenda               |
| Tread pattern                | K398A Polar Trac    |
| Antistatic                   | No                  |
| Tyre colour                  | Black               |
| ECE regulation number        | ECE 106             |
| Nettogewicht [kg] (gültig)   | 1,06                |
| Recommended rim size         | 2.10                |
| Maximum air pressure [bar].  | 1,40                |
| Section width (mm)           | 90                  |
| Outer diameter of tyre [mm]. | 282                 |
| Rolling circumference [mm].  | 842                 |
| E-Ready                      | No                  |

## Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|-------|--------------------|--------------|---------------|--------------------------|--------------|
| 14 A4 | 67                 | 20           | Drive Wheel   | 1,40                     | LLV          |
| 25 A4 | 92,50              | 20           | Free Rolling  | 1,40                     | LLV          |