# Bohnenkamp Moving Professionals

10.05.2025

### TYRES

Product group	Tyres	
Item number	19211160	
Valid tyre size	3.50 - 8	
LI / SI / PR	38 A4 / 49 A4, 4 PR	
TL/TT	тт	
SET	Tube	
Brand	Kenda	
Tread pattern	K406	



#### Notes and features

• All-purpose implement tyre.

• The grooved tread pattern is suitable for use on agricultural trailers, seeders and balers.

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

## Bohnenkamp Moving Professionals

### **Technical Informations**

Item number	19211160
EAN	5707562329482
Valid tyre size	3.50 - 8
LI / SI / PR	38 A4 / 49 A4, 4 PR
TL/TT	ТТ
SET	Tube
Valve designation	TR 13
Ventilposition	lateral
Brand	Kenda
Tread pattern	K406
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	2,20
Recommended rim size	2.50A
Maximum air pressure [bar].	2,75
Section width (mm)	96
Outer diameter of tyre [mm].	388
Rolling circumference [mm].	1158
E-Ready	No

### Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
38 A4	132	20	Drive Wheel	2,75	
49 A4	185	20	Free Rolling	2,75	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.