

TYRES

Product group	Tyres
Item number	19211167
Valid tyre size	4.80 / 4.00 - 8
LI / SI / PR	44 A4 / 55 A4, 4 PR
TL/TT	TT
SET	Tube
Brand	Kenda
Tread pattern	K406



Notes and features

- All-purpose implement tyre.
- The grooved tread pattern is suitable for use on agricultural trailers, seeders and balers.

Technical Informations

Item number	19211167
EAN	5707562329239
Valid tyre size	4.80 / 4.00 - 8
Alternative size 1	115/100-8
LI / SI / PR	44 A4 / 55 A4, 4 PR
TL/TT	TT
SET	Tube
Valve designation	TR 13
Ventilposition	lateral
Brand	Kenda
Tread pattern	K406
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	2,71
Recommended rim size	2.50A
Permitted rim size	3.75, 3.00
Maximum air pressure [bar].	2,80
Section width (mm)	110
Outer diameter of tyre [mm].	425
Rolling circumference [mm].	1268
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
44 A4	160	20	Drive Wheel	2,80	
55 A4	218	20	Free Rolling	2,80	