

TYRES

Product group	Tyres	
Item number	19211286	
Valid tyre size	22 x 9.50 - 10	
LI / SI / PR	75 A4 / 86 A4, 4 PR	
TL/TT	TL	
Brand	Kenda	
Tread pattern	K506	





Notes and features

- The Kenda K506 is a tyre for the maintenance of lawns and green areas.
- Its tread blocks have sipes to provide good traction and consequently optimum soil protection.
- Thanks to the spaces between the lugs and the extra deep tread depth, the tyre offers good self-cleaning properties.
- Due to the large contact area and the durable rubber compound, the tyre is particularly low-wear and durable.



Technical Informations

Item number	19211286
EAN	5707562265582
Valid tyre size	22 x 9.50 - 10
LI / SI / PR	75 A4 / 86 A4, 4 PR
TL/TT	TL
Brand	Kenda
Tread pattern	K506
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	7,63
Recommended rim size	7.001
Maximum air pressure [bar].	1,50
Section width (mm)	235
Outer diameter of tyre [mm].	546
Rolling circumference [mm].	1630
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
75 A4	387	20	Drive Wheel	1,50	
86 A4	530	20	Free Rolling	1,50	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.