

## **TYRES**

Product group	Tyres	
Item number	19211291	
Valid tyre size	24 x 12.00 - 10	
LI / SI / PR	77 A4 / 88 A4, 4 PR	
TL/TT	TL	
Brand	Kenda	
Tread pattern	K506	





## Notes and features

- The Kenda K506 is a tyre for the maintenance of lawns and green areas.
- Its tread blocks have sipes to provide good traction and consequently optimum soil protection.
- Thanks to the spaces between the lugs and the extra deep tread depth, the tyre offers good self-cleaning properties.
- Due to the large contact area and the durable rubber compound, the tyre is particularly low-wear and durable.



## **Technical Informations**

Item number	19211291
EAN	5707562270685
Valid tyre size	24 x 12.00 - 10
Alternative size 1	295/60-10
LI / SI / PR	77 A4 / 88 A4, 4 PR
TL/TT	TL
Brand	Kenda
Tread pattern	K506
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	11,67
Recommended rim size	8.00
Maximum air pressure [bar].	1,00
Section width (mm)	282
Outer diameter of tyre [mm].	610
Rolling circumference [mm].	1821
E-Ready	No

## **Load capacity**

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
77 A4	412	20	Drive Wheel	1,00	
88 A4	560	20	Free Rolling	1,00	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.