

TYRES

Product group	Tyres	
Item number	19266102	
Valid tyre size	155 / 70 R 12 C	
LI / SI / PR	104 / 102 N	
TL/TT	TL	
Brand	Kenda	
Tread pattern	KR101 MasterTrail 3G	





Notes and features

- The Kenda KR101 MasterTrail 3G is a tyre for single axle car trailers, tandem, tridem and other heavy trailers.
- The strong casing enables very high loading capacities.
- Due to its tread pattern, the tyre provides low rolling resistance, good wet grip and low noise.
- The high number of sipes ensures good dispersion of water, slush and snow for excellent driving performance all year round.
- The reinforced inner liner construction keeps the tyre particularly airtight and puncture-proof.



Technical Informations

Item number	19266102
EAN	5707562674544
Valid tyre size	155 / 70 R 12 C
LI / SI / PR	104 / 102 N
TL/TT	TL
Brand	Kenda
Tread pattern	KR101 MasterTrail 3G
M+S	M+S
Rolling resistance	В
Wet grip	С
Rolling noise [db].	72
Rolling noise level	В
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54,ECE 117
Nettogewicht [kg] (gültig)	5,90
Recommended rim size	4.503
Permitted rim size	4J, 5J
Maximum air pressure [bar].	6,50
Section width (mm)	157
Outer diameter of tyre [mm].	527
Stat. radius (SLR) [mm]	239
Rolling circumference [mm].	1597
Tread depth (mm)	5,8
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
104 N	900	140	Single	6,50	
102 N	850	140	Twin	6,50	