

## WHEELS

Product group	Wheels
Item number	58692160
Valid wheel size	225 / 55 R 12 C
Brand	Trailermaxx
Tread pattern	CR-966
Valid rim size	7.00 I x 12 H2
Rim connection	5/67/112
Bolt hole design	E12
Offset (mm)	10
Rim colour	Silver
Load capacity complete wheel [kg]	900
Speed complete wheel [km/h]	140
Nettogewicht [kg] (gültig)	16,93
RDA (Reifendruckregelanlage)	No
RDKS (Reifendruckkontrollsystem)	No



## Technical Informations

Assembly Item no. Tyres	• 10765030
LI / SI / PR	104 N, 8 PR
Load capacity 1 [kg]	900
Speed 1 [km/h].	140
Maximum air pressure [bar].	5,30
TL/TT	TL
M+S	M+S
Tyre colour	Black

E-Ready	No
Antistatic	No
ECE regulation number	ECE 54 ECE 117
Rolling resistance	C
Wet grip	B
Rolling noise [db].	69
Rolling noise level	A
Section width (mm)	232
Stat. radius (SLR) [mm]	255
Rolling circumference [mm].	1679
Assembly Item no. Rim	• 30810270
Load capacity of rim 1 [kg]	900
Speed Rims 1 [km/h]	140
Load capacity of rim 2 [kg]	950
Maximum speed [km/h].	140
Type of drive	Towed axle
Number of bolt holes	5
hub hole diameter [mm].	67
Bolt hole circle diameter [mm]	112
Bolt hole diameter [mm]	16
Countersinking	Sphere
Spherical countersink [mm].	R12
Rim centering	BC
Rim material	steel
RAL	RAL9006
Valve seat	External Valve
Ventilation holes	No

Single / multi-part	einteilig
Hump	H2
Cavity Sealed	No
Verschweißung beidseitig	No
Assembly Item no. Valve	• 47201095
Preassembled valve	No
TPMS-kompatibles Ventil	No
Valve hole diameter [mm]	11.3
Valve design	Metal valve
Valve length [mm]	42.0
Valve angle [°]	gerade