

WHEELS

| | |
|-----------------------------------|-----------------|
| Product group | Wheels |
| Item number | 59719829 |
| Valid wheel size | 155 / 70 R 12 C |
| Brand | BK Trailer |
| Tread pattern | 204 |
| Valid rim size | 4.5 J x 12 H2 |
| Rim connection | 5/67/112 |
| Bolt hole design | E12 |
| Offset (mm) | +20 |
| Rim colour | Silver |
| Load capacity complete wheel [kg] | 900 |
| Speed complete wheel [km/h] | 140 |
| Nettogewicht [kg] (gültig) | 13,03 |
| RDA (Reifendruckregelanlage) | No |
| RDKS (Reifendruckkontrollsystem) | No |



Technical Informations

| | |
|-----------------------------|-------------|
| Assembly Item no. Tyres | • 18545017 |
| LI / SI / PR | 104 / 102 N |
| Load capacity 1 [kg] | 900 |
| Speed 1 [km/h]. | 140 |
| Load capacity 3 [kg] | 850 |
| Speed 3 [km/h]. | 140 |
| Maximum air pressure [bar]. | 6,50 |
| TL/TT | TL |

| | |
|--------------------------------|----------------|
| M+S | M+S |
| Tyre colour | Black |
| E-Ready | No |
| Antistatic | No |
| ECE regulation number | ECE 54 ECE 117 |
| Rolling resistance | D |
| Wet grip | D |
| Rolling noise [db]. | 72 |
| Rolling noise level | B |
| Section width (mm) | 157 |
| Stat. radius (SLR) [mm] | 240 |
| Rolling circumference [mm]. | 1585 |
| Tread depth (mm) | 6,0 |
| Assembly Item no. Rim | • 39600636 |
| Load capacity of rim 1 [kg] | 900 |
| Speed Rims 1 [km/h] | 140 |
| Maximum speed [km/h]. | 140 |
| Type of drive | Towed axle |
| Number of bolt holes | 5 |
| hub hole diameter [mm]. | 67 |
| Bolt hole circle diameter [mm] | 112 |
| Bolt hole diameter [mm] | 16 |
| Countersinking | Sphere |
| Spherical countersink [mm]. | R12 |
| Rim centering | BC |
| Rim material | steel |
| RAL | RAL9006 |

| | |
|--------------------------|----------------|
| Valve seat | External Valve |
| Ventilation holes | No |
| Single / multi-part | einteilig |
| Hump | H2 |
| Cavity Sealed | No |
| Verschweißung beidseitig | No |
| Assembly Item no. Valve | • 47201095 |
| Preassembled valve | No |
| TPMS-kompatibles Ventil | No |
| Valve hole diameter [mm] | 11.3 |
| Valve design | Metal valve |
| Valve length [mm] | 42.0 |
| Valve angle [°] | gerade |