

WHEELS

Product group	Wheels
Item number	59915450
Valid wheel size	700 / 50 - 22.5
Brand	Alliance
Tread pattern	Flotation 331
Valid rim size	AG 24.00 x 22.5 TH2
Rim connection	8/221/275
Bolt hole design	A3
Rim colour	Red
Rim series	Profiline
Load capacity complete wheel [kg]	6700
Speed complete wheel [km/h]	40
Nettogewicht [kg] (gültig)	217,57
RDA (Reifendruckregelanlage)	No
RDKS (Reifendruckkontrollsystem)	No



Technical Informations

Assembly Item no. Tyres	• 15212655
LI / SI / PR	162 A8 / 174 A8, 16 PR
Load capacity 1 [kg]	4750
Speed 1 [km/h].	40
Load capacity 2 [kg]	6700
Speed 2 [km/h].	40
Maximum air pressure [bar].	2,40
TL/TT	TL

Tyre colour	Black
E-Ready	No
Antistatic	No
Direction	Right
ECE regulation number	ECE 106
Section width (mm)	700
Stat. radius (SLR) [mm]	550
Rolling circumference [mm].	3650
Tread depth (mm)	39,0
Assembly Item no. Rim	• 32012786
Load capacity of rim 1 [kg]	8040
Speed Rims 1 [km/h]	40
Load capacity of rim 2 [kg]	6640
Speed Rims 2 [km/h]	65
Maximum speed [km/h].	50
Type of drive	Angetriebene & gezogene Achse
Number of bolt holes	8
hub hole diameter [mm].	221
Bolt hole circle diameter [mm]	275
Bolt hole diameter [mm]	27
Bolt hole design EUWA	B22 ES 36
Countersinking	Sphere
Spherical countersink [mm].	R18
Rim centering	BC
Rim material	steel
RAL	RAL3000
Valve seat	External Valve

Ventilation holes	No
Single / multi-part	einteilig
Hump	TH2
Cavity Sealed	No
Knurling	without knurling
Verschweißung beidseitig	No
Assembly Item no. Valve	• 47201039
Preassembled valve	No
TPMS-kompatibles Ventil	No
Valve hole diameter [mm]	15.7
Valve design	Rubber valve
Valve length [mm]	55.0
Valve angle [°]	gerade