

WHEELS

| | |
|-----------------------------------|---------------------|
| Product group | Wheels |
| Item number | 59915551 |
| Valid wheel size | 700 / 50 - 22.5 |
| Brand | Alliance |
| Tread pattern | Flotation 331 |
| Valid rim size | AG 24.00 x 22.5 TH2 |
| Rim connection | 8/221/275 |
| Bolt hole design | A3 |
| Rim colour | Red |
| Rim series | Profiline |
| Load capacity complete wheel [kg] | 6700 |
| Speed complete wheel [km/h] | 40 |
| Nettogewicht [kg] (gültig) | 217,57 |
| RDA (Reifendruckregelanlage) | No |
| RDKS (Reifendruckkontrollsystem) | No |



Technical Informations

| | |
|-----------------------------|------------------------|
| Assembly Item no. Tyres | • 15212655 |
| LI / SI / PR | 162 A8 / 174 A8, 16 PR |
| Load capacity 1 [kg] | 4750 |
| Speed 1 [km/h]. | 40 |
| Load capacity 2 [kg] | 6700 |
| Speed 2 [km/h]. | 40 |
| Maximum air pressure [bar]. | 2,40 |
| TL/TT | TL |

| | |
|--------------------------------|-------------------------------|
| Tyre colour | Black |
| E-Ready | No |
| Antistatic | No |
| Direction | Left |
| ECE regulation number | ECE 106 |
| Section width (mm) | 700 |
| Stat. radius (SLR) [mm] | 550 |
| Rolling circumference [mm]. | 3650 |
| Tread depth (mm) | 39,0 |
| Assembly Item no. Rim | • 32012786 |
| Load capacity of rim 1 [kg] | 8040 |
| Speed Rims 1 [km/h] | 40 |
| Load capacity of rim 2 [kg] | 6640 |
| Speed Rims 2 [km/h] | 65 |
| Maximum speed [km/h]. | 50 |
| Type of drive | Angetriebene & gezogene Achse |
| Number of bolt holes | 8 |
| hub hole diameter [mm]. | 221 |
| Bolt hole circle diameter [mm] | 275 |
| Bolt hole diameter [mm] | 27 |
| Bolt hole design EUWA | B22 ES 36 |
| Countersinking | Sphere |
| Spherical countersink [mm]. | R18 |
| Rim centering | BC |
| Rim material | steel |
| RAL | RAL3000 |
| Valve seat | External Valve |

| | |
|--------------------------|------------------|
| Ventilation holes | No |
| Single / multi-part | einteilig |
| Hump | TH2 |
| Cavity Sealed | No |
| Knurling | without knurling |
| Verschweißung beidseitig | No |
| Assembly Item no. Valve | • 47201039 |
| Preassembled valve | No |
| TPMS-kompatibles Ventil | No |
| Valve hole diameter [mm] | 15.7 |
| Valve design | Rubber valve |
| Valve length [mm] | 55.0 |
| Valve angle [°] | gerade |