

## WHEELS

Product group	Wheels
Item number	59915611
Valid wheel size	750 / 45 R 22.5
Brand	Alliance
Tread pattern	380
Valid rim size	AG 24.00 x 22.5 TH2
Rim connection	10/281/335
Bolt hole design	A3
Offset (mm)	-50
Rim colour	Silver
Rim series	Profiline
Load capacity complete wheel [kg]	5300
Speed complete wheel [km/h]	70
Nettogewicht [kg] (gültig)	230,06
RDA (Reifendruckregelanlage)	No
RDKS (Reifendruckkontrollsystem)	No



 **ALLIANCE**

## Technical Informations

Assembly Item no. Tyres	• 15215660
LI / SI / PR	169 D / 166 E
Load capacity 1 [kg]	5800
Speed 1 [km/h].	70
Load capacity 2 [kg]	5300
Maximum air pressure [bar].	4,00
TL/TT	TL

Tyre colour	Black
E-Ready	No
Carcass properties	Steel Belted
Antistatic	No
ECE regulation number	ECE 106
Section width (mm)	750
Stat. radius (SLR) [mm]	568.00
Rolling circumference [mm].	3815
Tread depth (mm)	25,5
Assembly Item no. Rim	• 32012784
Load capacity of rim 1 [kg]	8040
Speed Rims 1 [km/h]	40
Load capacity of rim 2 [kg]	6640
Speed Rims 2 [km/h]	65
Maximum speed [km/h].	70
Type of drive	Angetriebene & gezogene Achse
Number of bolt holes	10
hub hole diameter [mm].	281
Bolt hole circle diameter [mm]	335
Bolt hole diameter [mm]	27
Bolt hole design EUWA	B22 ES 36
Countersinking	Sphere
Spherical countersink [mm].	R18
Rim centering	BC
Rim material	steel
RAL	RAL9006
Valve seat	External Valve

Ventilation holes	No
Single / multi-part	einteilig
Hump	TH2
Cavity Sealed	No
Knurling	without knurling
Verschweißung beidseitig	No
Assembly Item no. Valve	• 47201039
Preassembled valve	No
TPMS-kompatibles Ventil	No
Valve hole diameter [mm]	15.7
Valve design	Rubber valve
Valve length [mm]	55.0
Valve angle [°]	gerade