

WHEELS

Product group	Wheels
Item number	60023253
Valid wheel size	520 / 85 R 42
Brand	Alliance
Tread pattern	385
Valid rim size	DW 18 L x 42
Rim connection	10/281/335
Bolt hole design	B3
Offset (mm)	+100
Rim colour	Silver
Load capacity complete wheel [kg]	5600
Speed complete wheel [km/h]	40
Nettogewicht [kg] (gültig)	379.91
RDA (Reifendruckregelanlage)	No
RDKS (Reifendruckkontrollsystem)	No



Technical Informations

Assembly Item no. Tyres	• 15227399
LI / SI / PR	168 A8 / 165 D
Load capacity 1 [kg]	5600
Speed 1 [km/h].	40
Load capacity 2 [kg]	5150
Speed 2 [km/h].	65
Maximum air pressure [bar].	2,80
TL/TT	TL

Tyre colour	Black
E-Ready	No
Carcass properties	High Speed
Antistatic	No
ECE regulation number	ECE 106
Section width (mm)	538
Stat. radius (SLR) [mm]	901
Speed Radius Index (SRI)	925
Rolling circumference [mm].	5947
Tyre capacity 75% [ltr.]	531
Assembly Item no. Rim	• 39123027
Load capacity of rim 1 [kg]	7500
Speed Rims 1 [km/h]	40
Load capacity of rim 2 [kg]	8070
Speed Rims 2 [km/h]	65
Maximum speed [km/h].	50
Type of drive	Angetriebene & gezogene Achse
Number of bolt holes	10
hub hole diameter [mm].	281
Bolt hole circle diameter [mm]	335
Bolt hole diameter [mm]	27
Bolt hole design EUWA	B22 DS 36
Countersinking	Sphere
Spherical countersink [mm].	R18
Rim centering	BC
Rim material	steel
Colour type	Glossy

RAL	RAL9006
Valve seat	External Valve
Ventilation holes	No
Single / multi-part	einteilig
Hump	kein Hump
Valve protection	VSH
Surface treatment	SB
Cavity Sealed	No
Verschweißung beidseitig	No
Assembly Item no. Valve	• 47201038
Preassembled valve	No
TPMS-kompatibles Ventil	No
Valve hole diameter [mm]	15.7
Valve design	Metal valve
Valve designation ETRTO	V5.01.1
Valve length [mm]	50.0
Valve angle [°]	gerade