

## WHEELS

|                                   |               |
|-----------------------------------|---------------|
| Product group                     | Wheels        |
| Item number                       | 60023258      |
| Valid wheel size                  | 520 / 85 R 42 |
| Brand                             | Alliance      |
| Tread pattern                     | 385           |
| Valid rim size                    | DW 18 L x 42  |
| Rim connection                    | 10/281/335    |
| Bolt hole design                  | B3            |
| Offset (mm)                       | -75           |
| Rim colour                        | Silver        |
| Load capacity complete wheel [kg] | 5150          |
| Speed complete wheel [km/h]       | 65            |
| Nettogewicht [kg] (gültig)        | 372,31        |
| RDA (Reifendruckregelanlage)      | No            |
| RDKS (Reifendruckkontrollsystem)  | No            |



## Technical Informations

|                             |                |
|-----------------------------|----------------|
| Assembly Item no. Tyres     | • 15227399     |
| LI / SI / PR                | 168 A8 / 165 D |
| Load capacity 1 [kg]        | 5600           |
| Speed 1 [km/h].             | 40             |
| Load capacity 2 [kg]        | 5150           |
| Speed 2 [km/h].             | 65             |
| Maximum air pressure [bar]. | 2,80           |
| TL/TT                       | TL             |

|                                |                               |
|--------------------------------|-------------------------------|
| Tyre colour                    | Black                         |
| E-Ready                        | No                            |
| Carcass properties             | High Speed                    |
| Antistatic                     | No                            |
| ECE regulation number          | ECE 106                       |
| Section width (mm)             | 538                           |
| Stat. radius (SLR) [mm]        | 901                           |
| Speed Radius Index (SRI)       | 925                           |
| Rolling circumference [mm].    | 5947                          |
| Tyre capacity 75% [ltr.]       | 531                           |
| Assembly Item no. Rim          | • 39123036                    |
| Load capacity of rim 1 [kg]    | 8070                          |
| Speed Rims 1 [km/h]            | 65                            |
| Maximum speed [km/h].          | 65                            |
| Type of drive                  | Angetriebene & gezogene Achse |
| Number of bolt holes           | 10                            |
| hub hole diameter [mm].        | 281                           |
| Bolt hole circle diameter [mm] | 335                           |
| Bolt hole diameter [mm]        | 27                            |
| Bolt hole design EUWA          | B22 DS 36                     |
| Countersinking                 | Sphere                        |
| Spherical countersink [mm].    | R18                           |
| Rim centering                  | BC                            |
| Rim material                   | steel                         |
| RAL                            | RAL9006                       |
| Valve seat                     | External Valve                |
| Ventilation holes              | No                            |

|                          |             |
|--------------------------|-------------|
| Single / multi-part      | einteilig   |
| Hump                     | kein Hump   |
| Valve protection         | VSH         |
| Cavity Sealed            | No          |
| Verschweißung beidseitig | No          |
| Assembly Item no. Valve  | • 47201038  |
| Preassembled valve       | No          |
| TPMS-kompatibles Ventil  | No          |
| Valve hole diameter [mm] | 15.7        |
| Valve design             | Metal valve |
| Valve designation ETRTO  | V5.01.1     |
| Valve length [mm]        | 50.0        |
| Valve angle [°]          | gerade      |